

LS

September 2019

NAME

ls - list directory contents

SYNOPSIS

ls [*OPTION*]... [*FILE*]...

DESCRIPTION

List information about the FILES (the current directory by default). Sort entries alphabetically if none of **-cftuvSUX** nor **--sort** is specified.

Mandatory arguments to long options are mandatory for short options too.

-a, --all do not ignore entries starting with **.**

-A, --almost-all do not list implied **.** and **..**

--author with **-l**, print the author of each file

-b, --escape print C-style escapes for nongraphic characters

--block-size=SIZE with **-l**, scale sizes by SIZE when printing them; e.g., **'--block-size=M'**; see SIZE format below

-B, --ignore-backups do not list implied entries ending with **~**

-c with **-lt**: sort by, and show, ctime (time of last modification of file status information); with **-l**: show ctime and sort by name; otherwise: sort by ctime, newest first

-C list entries by columns

--color[=WHEN] colorize the output; WHEN can be 'always' (default if omitted), 'auto', or 'never'; more info below

-d, --directory list directories themselves, not their contents
-D, --dired generate output designed for Emacs' dired mode
-f do not sort, enable **-aU**, disable **-ls --color**
-F, --classify append indicator (one of */=>@|) to entries
--file-type likewise, except do not append '*'
--format=WORD across **-x**, commas **-m**, horizontal **-x**, long **-l**, single-column **-l**, verbose **-l**, vertical **-C**
--full-time like **-l --time-style=full-iso**
-g like **-l**, but do not list owner
--group-directories-first group directories before files;
 can be augmented with a **--sort** option, but any use of **--sort=none (-U)** disables grouping
-G, --no-group in a long listing, don't print group names
-h, --human-readable with **-l** and **-s**, print sizes like 1K 234M 2G etc.
--si likewise, but use powers of 1000 not 1024
-H, --dereference-command-line follow symbolic links listed on the command line
--dereference-command-line-symlink-to-dir follow each command line symbolic link
 that points to a directory
--hide=PATTERN do not list implied entries matching shell PATTERN (overridden by **-a** or **-A**)
--hyperlink[=WHEN] hyperlink file names; WHEN can be 'always' (default if omitted), 'auto', or 'never'
--indicator-style=WORD append indicator with style WORD to entry names: none (default), slash (**-p**), file-type (**--file-type**), classify (**-F**)
-i, --inode print the index number of each file
-I, --ignore=PATTERN do not list implied entries matching shell PATTERN
-k, --kibibytes default to 1024-byte blocks for disk usage; used only with **-s** and per directory totals
-l use a long listing format

-L, --dereference when showing file information for a symbolic link, show information for the file the link references rather than for the link itself

-m fill width with a comma separated list of entries

-n, --numeric-uid-gid like **-l**, but list numeric user and group IDs

-N, --literal print entry names without quoting

-o like **-l**, but do not list group information

-p, --indicator-style=*slash* append / indicator to directories

-q, --hide-control-chars print ? instead of nongraphic characters

--show-control-chars show nongraphic characters as-is (the default, unless program is 'ls' and output is a terminal)

-Q, --quote-name enclose entry names in double quotes

--quoting-style=*WORD* use quoting style *WORD* for entry names: literal, locale, shell, shell-always, shell-escape, shell-escape-always, c, escape (overrides `QUOTING_STYLE` environment variable)

-r, --reverse reverse order while sorting

-R, --recursive list subdirectories recursively

-s, --size print the allocated size of each file, in blocks

-S sort by file size, largest first

--sort=*WORD* sort by *WORD* instead of name: none (**-U**), size (**-S**), time (**-t**), version (**-v**), extension (**-X**)

--time=*WORD* with **-l**, show time as *WORD* instead of default modification time: atime or access or use (**-u**); ctime or status (**-c**); also use specified time as sort key if **--sort=*time*** (newest first)

--time-style=*TIME_STYLE* time/date format with **-l**; see `TIME_STYLE` below

-t sort by modification time, newest first

-T, --tabsize=*COLS* assume tab stops at each *COLS* instead of 8

-u with **-lt**: sort by, and show, access time; with **-l**: show access time and sort by name; otherwise: sort by access time, newest first

-U do not sort; list entries in directory order

-v natural sort of (version) numbers within text

-w, --width=*COLS* set output width to *COLS*. 0 means no limit

- x list entries by lines instead of by columns
- X sort alphabetically by entry extension
- Z, --context print any security context of each file
- l list one file per line. Avoid '\n' with -q or -b
- help display this help and exit
- version output version information and exit

The SIZE argument is an integer and optional unit (example: 10K is 10*1024). Units are K,M,G,T,P,E,Z,Y (powers of 1024) or KB,MB,... (powers of 1000).

The TIME_STYLE argument can be full-iso, long-iso, iso, locale, or +FORMAT. FORMAT is interpreted like in date(1). If FORMAT is FORMAT1<newline>FORMAT2, then FORMAT1 applies to non-recent files and FORMAT2 to recent files. TIME_STYLE prefixed with 'posix-' takes effect only outside the POSIX locale. Also the TIME_STYLE environment variable sets the default style to use.

Using color to distinguish file types is disabled both by default and with --color=*never*. With --color=*auto*, ls emits color codes only when standard output is connected to a terminal. The LS_COLORS environment variable can change the settings. Use the dircolors command to set it.

Exit status:

- 0 if OK,
- 1 if minor problems (e.g., cannot access subdirectory),
- 2 if serious trouble (e.g., cannot access command-line argument).

AUTHOR

Written by Richard M. Stallman and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>
Report ls translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>. This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<https://www.gnu.org/software/coreutils/ls>> or available locally via: info '(coreutils) ls invocation'